

# SealBoss®

## 6500 HM QuickFix



Product Data Sheet  
Hand Mix Polyurea Filler

### Product Description

**SealBoss® 6500 HM QuickFix** is a technologically advanced, two component, 7:1 ratio, 100% solids, flexible polyurea elastomer product with a retarded pot life.

SealBoss® 6500 HM QuickFix is a high quality joint and crack filler for concrete substrates in applications that are time critical. It works well in adverse temperature conditions as the material cures in ambient temperatures from -28°C (-20°F) to 54°C (130°F). The tack free time is 5 to over 15 minutes depending on temperature. This permits to reopen the jobsite to vehicle and foot traffic just one hour after the application. Exposure to sunlight (UV) may cause discoloration, however the physical properties are essentially unaffected. Ask your SealBoss technician for details. The product is for professional use.

### Installation Guidelines

Clean the area of debris and contaminants, such as oils, loose materials, dirt, rubber etc., to allow for good adhesion of the product. Expose clean rough concrete for best results. If using a saw to cut concrete and clean the crack, remove all the dust from the cut out area. Make sure the area is dry. All equipment, pumps and hoses must be dry. Avoid moisture contact with the mixture.

For bulk mixing, pre-mix each component thoroughly. Proportion parts at 7:1 ratio by volume of Component "A" and Component "B" preferably by mixing the B side into the A side container. Mix only the quantity that can be used within the pot life of the product. The material can be mixed with sand or quartz sand and other approved fillers in a ratio of up to 30%. Use of filled product will prolong the reaction time. Do not add solvents or thinners. They will prevent proper cure. Not for sealing cracks and joints under hydrostatic pressure or with extreme movement. Material is a vapor barrier after cure. Minimum age of concrete must be 21-28 days, depending on curing and drying conditions prior to applications.

### Maintenance of Equipment

Tools and equipment must be cleaned immediately after use. Remove all excess product. Cured product is hard to remove. **SealBoss® R70 Pump Flush** is a solvent free, non-flammable cleaner, lubricator, pump and hose conditioner. Please refer to the product data sheet for detailed information.

### Health and Safety

Protect your health! Always use safety gear in compliance with OSHA and all applicable local and job-site regulations while working with products. Handling of this product may result in spills, splashes, and airborne substances. Wear appropriate safety goggles, gloves and safety clothing at all times. Consider property in proximity of the application to prevent loss or damage. Protect jobsite from unauthorized persons. Store all materials and equipment safely and out of reach of children and

### Extended Pot Life Joint Filler & Joint Repair System

#### SealBoss® 6500 HM QuickFix Applications

- To fill cracks, damaged control joints, construction joints on horizontal concrete
- For industrial floor applications which receive heavy vehicle traffic, such as fork lifts or steel wheeled carts
- Highly flexible, allowing slab movement, yet strong enough to protect the vertical edges of concrete from spalling under heavy loading
- Interior and exterior use, discoloration in prolonged UV exposure

#### SealBoss® 6500 HM QuickFix Advantages

- 100% Solids and VOC Free
- Remains Flexible, Even in Cold Temperatures
- Return Project to Service in 60 Minutes
- Cures From -0-54°C / 32-130°F
- Reduced Moisture Sensitivity
- Essentially Odorless
- Resistant to Petrochemicals

#### Typical Application Environments

- Industrial Facilities
- Warehouse Floors
- Manufacturing Facilities
- Pulp and Paper Mills
- Bottling and Canning Facilities
- Airports
- Water and Waste Water Treatment
- Cold Storage Facilities
- Food Processing Facilities

animals! Observe container labels, SDS, applicable laws and regulations and all instructions before using the product and equipment. In case one of the components comes in contact with the skin, wash thoroughly with soap and water. Provide adequate ventilation in volume and pattern in working area. Further protection: emergency showers and eyewash stations. Get immediate medical attention as needed.

SealBoss® 6500 HM QuickFix

# SealBoss®

## 6500 HM QuickFix



### Product Data Sheet Hand Mix Polyurea Filler

#### Technical Data

##### PHYSICAL PROPERTIES:

Color (A+B)

Viscosity (mixed)

Mix Ratio (by volume)

Pot Life 0.1 kg at 25°C / 77°F

Tack Free , Thin Film at 25°C / 77°F

Initial Cure at 25°C / 77°F

Final Cure at 25°C / 77°F

% of Elongation

Service Movement

Tensile Strength, psi

Bond Strength, fully cured clean concrete, psi

Tear Strength, pli, Die C

Shore "A" Hardness

Resistance to Chemicals

Charcoal Grey,  
Black, or other

Self Leveling

7:1

8-12 min

40-50 min

120 min

5 days

600

ASTM D-412

± 20%

>2100

ASTM D-412

400

ASTM C-882

>450

ASTM D-624

80-85A

ASTM D-2240

Resistant to Most Organic Solvents,  
Mild Acids, Alkali and  
Micro Organisms

##### PACKAGING:

Units

Shelf Life:

Storage Conditions:

Disposal:

1 gal kit, 0.825 gal A / 0.172 gal B, 7:1 ratio by volume

6 months in original unopened container

Store at 55-95°F

In accordance with all applicable laws and regulations

Empty containers must be drip free

##### Chemical Resistance:

Test Procedure; ASTM D-1308 at 72°F

R=Recommend

RC=Recommend Conditional, some swelling  
or discoloration

N=Not Recommend

1=Some discoloration only

Chemical Result

Acetic Acid 10 % R

Acetone RC

Battery Acid (Sulfuric Acid) RC

Brake fluid R

Chlorine (2,000ppm in H<sub>2</sub>O) R

Citric Acid R

Gasoline R

Hydraulic Oil R-1

Methanol (5%) Gasoline RC


Motor Oil R-1

Toluene RC

Vinegar R

Water R

Xylene R



**Limited Warranty Policy and Disclaimer for Products Supplied and/or Distributed by SealBoss Corp.:** SealBoss Corp. Products are for Professional Use. All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty either expressed or implied. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any supplied materials relieves the user of the obligation to read and follow the warnings and instruction for each product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use. SealBoss Corp. warrants supplied / distributed products to be free of manufacturing defects. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of the manufacturer which proves to be defective. There are no other warranties by SealBoss Corp. of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. SealBoss Corp. shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty whether expressed or implied. SealBoss Corp. shall not be responsible for use of this product in a manner to infringe on any patent or any other intellectual property rights held by others. In addition, no warranty or guarantee is being issued with respect to appearance, color, fading, chalking, staining, shrinkage, peeling, UV damage, excessive temperature exposure, normal wear and tear or improper application by the applicator. Damage caused by abuse, neglect and lack of proper maintenance, acts of nature and / or physical movement of the substrate or structural defects are also excluded from the limited warranty. SealBoss Corp. reserves the right to conduct performance tests on any material claimed to be defective prior to any repairs by owner, general contractor, or applicator. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations and statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller. SealBoss Corp. reserves the right to change the properties of products without notice.

Revised 201705