

JointMaster Pro2 G3i Digital Two Component Joint Filler Pump



- **Design** G3i Industrial Grade Design with New Features
- **Frame** Robust, Modern & Sleek Steel Design, Stronger & Smaller Footprint
- **Pumps** Advanced Gear Pump System, Improved Flow Rate & Seals
- **Motor** Industrial, CE Grade Engineered High Tech Motor
- **Digital** Programmable Logic Controller with Digital Display
- **Applicator** Low Amp/Volt Safety Control Line to Applicator with Control Dial

Welcome to the Digital Age in Floor Repair

- Professional Use
- Two-Component
- Joint Sealer
- Highway Joint / Crack Repair
- Polyurea
- Polyurethane
- Epoxy

Inside and Outside Applications

- Warehouses
- Parking Structures
- Highway Repair
- Driveways
- Control Joints

Custom Equipped to Your Order

- Tank Volume
- Tank Material
- Manifold Cleaning Options
- Heater Band Option
- Battery & Inverter Option
- Generator Option
- 110 Volt Standard
- 220 Volt International Markets




Two Component Joint Filler Pump

Pro2 G3i Digital

JointMaster

JointMaster Pro2 G3i Digital Two Component Joint Filler Pump

We Listened - Implementing Over 10 Years of Experience and Customer Feedback.



- The New JointMaster Pro2 Gen3i is Designed for a Wide Variety of Joint Filler Products
- New Pump Units, 10 Times Improved Seal Pressure Resistance, Thicker Product Compliance
- New Programmable Digital Motor Control with Display for Consistent Product Flow & Higher Output
- Safety - Low Voltage Signal Line to Applicator
- New CE Rated Motor with Much Lower Energy Consumption - Run Longer on Battery!
- Improved, Fully Enclosed Drive Design, 3 Shaft, Reduced Friction Energy Saving Design
- New Frame Design - Smaller Footprint, Quality Fit & Finish, Better Handling, Stronger Frame
- Very High Build Quality, Sharp and Professional on the Jobsite, Enhance Your Company's Image
- Stainless Steel Tanks Standard, other Options Available
- Custom Equipped - Tank Size, Battery & Applicator Options
- International Versions, 110V, 220V, 50-60Hz

Specifications

Weight:	Basic Pump 205 lbs. dry. Extra equipment not included.
Height:	44" (5 gal tanks) , 47" (6 gal tanks) Width: 25", Length: 29.5"
Motor:	1/2 [hp], ~200 [lb-in], AC Gear
Pumps:	Internal rotary gear pumps
Tanks:	5 gal/ 6 gal, 14 gauge 304 stainless steel
Power:	110 V 5 A, 220 V version available
Hoses:	3/8" x 14.5' braided, protective sleeve
Wheels:	6" , swivel wheels with brakes
Control:	Extended lightweight handle, dual port manifold, digital speed control. Low voltage control line to applicator Programmable Digital Control
Viscosity:	approx. 50 – 4000 cps, depending on material, please call
Flow Rate:	approx. 0.1 to over 1 gallon per minute
Ratios:	1:1 by volume ratio standard, other ratios available

SealBoss® QuickFix Joint Filler & Spall Repair Products



SealBoss® Corp. recommends SealBoss® QuickFix Products for use with the JointMaster Pro2 pump systems.



Please contact a SealBoss® representative for detailed information and to confirm that your product is suitable for use with this machine. Specific product data sheet and MSDS of product to be intended for use will help you to determine the suitability. Please refer to the JointMaster Pro2 G3i Digital Manual for more information. Due to the nature of a dispensing machine like the JointMaster Pro2, user shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any materials supplied or distributed by SealBoss® Corp. relieves the user of the obligation to read and follow the warnings and instruction for each SealBoss® Corp. product as set forth in the current Technical Data Sheet, product label and Material Safety Data Sheet prior to product use. SealBoss® Corp. warrants its products to be free of manufacturing defects. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of the manufacturer which proves to be defective. There are no other warranties by SealBoss® Corp. of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. SealBoss® Corp. specifically does not take back or restock any used equipment. SealBoss® Corp. does not apply credit for used equipment.

20150900