



SealBoss® Seal Oakum Applications

- For Use With SealBoss Hydro Active PU Water Stop Foam Injection Grouts
- Stop Water Infiltration Through Larger Openings, Cracks, And Voids
- Create Or Use In Combination With Joint Gaskets In Sewer And Storm Drain Lines, Ducts
- Wastewater Treatment Plants
- Reservoirs and Water Tanks
- Pipelines, Duct Works
- Service Manholes
- Tunnels and Underground Cable Trenches
- Industrial Buildings, Power Plants
- Commercial and Public Utility Buildings

Product Description

SealBoss® 1500 Seal Oakum is a tar free (dry oakum), strong, jute based material designed to soak up SealBoss® WaterStopFoam products and injection grouts, while keeping products in place to create a barrier in larger openings of active water infiltration.

Installation Guidelines

Submerge SealBoss® 1500 Seal Oakum into activated foam resin. When removing from container, wipe off excess material. If necessary, wet joints or voids with water to prime surface for saturated SealBoss® 1500 Seal Oakum. To seal minor leaks, dip saturated SealBoss® 1500 Seal Oakum into water to start reaction. Place saturated SealBoss® 1500 Seal Oakum in the joint or void. You may spray visible saturated SealBoss® 1500 Seal Oakum surface with water to speed up the cure process. Cut excess from surface of joint after cure. To achieve most satisfying and permanent results in certain applications, a combination of **SealBoss® 1510 Water Stop Foam** with other systems of our product line may be advised. Ask your SealBoss® technician for details. The product is for professional use.

Federal Specification: SealBoss® 1500 Seal Oakum conforms to Federal Specification HH-P-117 as published in the Federal Standard Stock Catalog, Section IV Part 5. HHP- 117 was approved by the Director of Procurement on November 5, 1940 for the use of all departments and establishments of the Government. Copies are available from the Superintendent of Documents, Washington, D.C. The specification covers twisted jute packing only.

Limited Warranty Policy and Disclaimer for Products Supplied and/or Distributed by SealBoss Corp.: SealBoss Corp. Products are for Professional Use. All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty either expressed or implied. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any supplied materials relieves the user of the obligation to read and follow the warnings and instruction for each product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use. SealBoss Corp. warrants supplied / distributed products to be free of manufacturing defects. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of the manufacturer which proves to be defective. There are no other warranties by SealBoss Corp. of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. SealBoss Corp. shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty whether expressed or implied. SealBoss Corp. shall not be responsible for use of this product in a manner to infringe on any patent or any other intellectual property rights held by others. In addition, no warranty or guarantee is being issued with respect to appearance, color, fading, chalking, staining, shrinkage, peeling, UV damage, excessive temperature exposure, normal wear and tear or improper application by the applicator. Damage caused by abuse, neglect and lack of proper maintenance, acts of nature and / or physical movement of the substrate or structural defects are also excluded from the limited warranty. SealBoss Corp. reserves the right to conduct performance tests on any material claimed to be defective prior to any repairs by owner, general contractor, or applicator. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations and statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller. SealBoss Corp. reserves the right to change the properties of products without notice.

Case: 50 lbs
700ft (213 m),
7-strands twisted



Packaging

Bag - 0.7 lbs	7 pieces, 1 ft each
Box - 6.5 lbs	7 pieces, 10 ft each
Case 50 lbs	approx. 700 ft (213 m), 7 strands twisted

Storage

Store in temperatures between 60–100°F (16–38°C) in a dry atmosphere. Keep in a sealed container away from moisture. Keep away from flammables or open flames.

Health and Safety

Protect your health! Always use safety gear in compliance with OSHA and all applicable local and job-site regulations while working with products. Handling of this product may result in spills, splashes, and airborne substances. Wear appropriate safety goggles, gloves and safety clothing at all times. During the pressure injection process a full face shield is advised for anybody within reach of product spill or blowout. Consider property in proximity of the application to prevent loss or damage. Protect jobsite from unauthorized persons. Store all materials and equipment safely and out of reach of children and animals! Observe container labels, SDS, applicable laws and regulations and all instructions before using the product and equipment. In case one of the components comes in contact with the skin, wash thoroughly with soap and water. Provide adequate ventilation in volume and pattern in working area. Further protection: emergency showers and eyewash stations. Get immediate medical attention as needed.

