

SealBoss® GeoTech Line

- Membrane Pump IP-GT1C-SS has a delivery max of .5 GPM (1.9 lpm)
- Single component pump suitable for Epoxy and polyurethane grouts
- Stainless steel construction suitable for most chemical grouts
- Pressure gauge readings accurate from 0-3000 psi (200 bar)

Applications

- Polyurethane Injection
- Pre-mixed Epoxy Injection
- Crack Injection
- Water Control Grouting
- Permeation Grouting
- Compaction Grouting

Sold Separately

- Injection Packers
- Injection Lances
- Pump Flush


Operation

- Electric
- Single Component Materials
- Stainless Steel Construction
- Recirculation Line for Pressure Relief
- High Quality Construction



Technical Data

Working Pressure:	0-3000 psi (200 bar)
Delivery:	max 0.5 GPM / 1.9 lpm
Motor Voltage:	110V
Weight:	48 lb / 22 kg
Dimensions:	30" x 11" x 23"



Limited Warranty Policy and Disclaimer for Products Supplied and/or Distributed by SealBoss Corp.: SealBoss Corp. Products are for Professional Use. All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty either expressed or implied. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any supplied materials relieves the user of the obligation to read and follow the warnings and instruction for each product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use. SealBoss Corp. warrants supplied / distributed products to be free of manufacturing defects. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of the manufacturer which proves to be defective. There are no other warranties by SealBoss Corp. of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. SealBoss Corp. shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty whether expressed or implied. SealBoss Corp. shall not be responsible for use of this product in a manner to infringe on any patent or any other intellectual property rights held by others. In addition, no warranty or guarantee is being issued with respect to appearance, color, fading, chalking, staining, shrinkage, peeling, UV damage, excessive temperature exposure, normal wear and tear or improper application by the applicator. Damage caused by abuse, neglect and lack of proper maintenance, acts of nature and / or physical movement of the substrate or structural defects are also excluded from the limited warranty. SealBoss Corp. reserves the right to conduct performance tests on any material claimed to be defective prior to any repairs by owner, general contractor, or applicator. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations and statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller. SealBoss Corp. reserves the right to change the properties of products without notice.

Revised 201705