

SealBoss® SB Formula Advantages

- Ready to Use Formula, Cleans with Water
- Horizontal or Vertical Poured Concrete
- User-Friendly Water Dilution
- Waterproofing and Repelling Properties
- Vapor Barriers
- Residential and Commercial Applications
- Masonry and Concrete Block Surfaces
- Dustproofing Properties
- Interior Air Quality Benefits
- Maintains Surface Appearance



How SB Formula Works

SealBoss® SB Formula contains microscopic particles that trigger a chemical reaction with lime, calcium and alkaline components in concrete creating CSH (Calcium Silicate Hydrate).

CSH provides waterproofing, repelling and strengthening properties to the natural concrete surface. It also provides a stronger, smoother and shinier surface.

SealBoss® offers decades of experience, successful results and developments in the waterproofing industry.

Product Description

SealBoss® SB Formula is a technologically advanced water-based, chemically reactive, transparent, vapor impermeable concrete and masonry penetrating sealer for poured and block concrete substrates. The cured crystallized product waterproofs, preserves, protects, and strengthens substrates while also minimizing vapor and radon gas migration.

SealBoss® SB Formula is supplied as a ready to use full strength formula solution. Ask your SealBoss® technician for details. The product is for professional use.

Installation Guidelines

The concrete should be fully cured, free of debris, oils, stains, etc. Do not apply sealer to an existing coating or sealant. Test the porosity of the substrate with water to ensure that the surface is accepting sealant solution. Note: It is not recommended to apply the sealer to excessively porous concrete.

Mix and use SealBoss® SB Formula. Do not dilute. Apply sealant to substrate with a coverage rate of 800-1000 sq ft/gal of mixed solution. A two coat process is recommended for adequate sealing, dustproofing, strengthening, and protecting (approximately 30-60 minutes apart depending on temperature and conditions). Apply to the surface by spraying, brushing or mopping. Excessive sealant should be worked into the substrate.

SealBoss® SB Formula is a proprietary solution blend that maximizes penetration within the bare concrete surface providing an industry-leading protection. The product contains microscopic particles of silicate, a mineral that will penetrate past the surface pores of the concrete substrate and trigger a chemical reaction within the concrete. During this process it creates Calcium Silicate Hydrate (CSH) while reacting with the free lime, calcium, and various alkaline components inside the concrete. CSH aids in increasing the waterproofing, repelling and strengthening properties of the natural concrete. It also provides a smoother and shinier surface.

Excessive application of SealBoss® SB Formula may result in


white residue and deposits on the surface of the substrate. Residue can be brushed clean with warm water and brush treatment. Previously sealed concrete will prevent penetration. Ambient temperatures should be in the range of 36F to 135F (2°C to 57°C). Condition product to room temperature in cold climate. The product is not intended as a decorative sealant and not for extremely porous concrete such as block masonry with voids and large air pockets. The product is not a primary concrete strengthening agent. Deterioration in concrete due to inadequate batching or application techniques may cause ultimate concrete failures.

Equipment

Standard spray equipment can be used for application of at the recommended application coverages. Over-spray and excessive application will not enhance effects and properties. Equipment must be cleaned sufficiently with water in order to fully dilute and purge all traces of solution within in the pump and delivery systems.

Health and Safety

Protect your health! Always use safety gear in compliance with OSHA and all applicable local and job-site regulations While working with products. Handling of this product may result in spills, splashes, and airborne substances. Wear appropriate safety goggles, gloves and safety clothing at all times. Protect jobsite from unauthorized persons. Store all materials and equipment safely and out of reach of children and animals! Observe container labels, SDS, applicable laws and regulations and all instructions before using the product and equipment. In case one of the components comes in contact with the skin, wash thoroughly with soap and water. Get immediate medical attention as needed.



Technical Properties

Appearance	Clear Liquid
Solids	100%
Specific Gravity	1.4 g/cm ³ (20°C)
pH	11.3
Viscosity, cps	400cps concentrate - approx. 100 cps diluted
Mixing	Mix full strength SB Formual prior to use
Ambient Application Temp. Range	36°F to 135°F (2°C to 57°C) Condition product to room temperature in cold climate
Density	11.8 lbs/gal
Packaging	1 gal 5 gal 55 gal
Storage	Good storage stability for unopened containers at 5-25°C 40-80°F in dry, sun free indoors environment 1 year shelf life. Properties for Cured Product May Vary
Corrosiveness	Non-Corrosive
Appearance	White Crystallization
Trafficable	Allow 24 hours for pedestrian and vehicular traffic
Recoat	Allow 45 minutes - 1 hour between coats



Limited Warranty Policy and Disclaimer for Products Supplied and/or Distributed by SealBoss Corp.: SealBoss Corp. Products are for Professional Use. All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty either expressed or implied. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any supplied materials relieves the user of the obligation to read and follow the warnings and instruction for each product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use. SealBoss Corp. warrants supplied / distributed products to be free of manufacturing defects. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of the manufacturer which proves to be defective. There are no other warranties by SealBoss Corp. of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. SealBoss Corp. shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty whether expressed or implied. SealBoss Corp. shall not be responsible for use of this product in a manner to infringe on any patent or any other intellectual property rights held by others. In addition, no warranty or guarantee is being issued with respect to appearance, color, fading, chalking, staining, shrinkage, peeling, UV damage, excessive temperature exposure, normal wear and tear or improper application by the applicator. Damage caused by abuse, neglect and lack of proper maintenance, acts of nature and / or physical movement of the substrate or structural defects are also excluded from the limited warranty. SealBoss Corp. reserves the right to conduct performance tests on any material claimed to be defective prior to any repairs by owner, general contractor, or applicator. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations and statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller. SealBoss Corp. reserves the right to change the properties of products without notice.

Revised 201705