



TRUESDAIL LABORATORIES, INC.

Product Listing

For:

Drinking Water System Components – Health Effects

Company:

SealBoss Corporation
1669 E Wilshire Avenue
Santa Ana, CA 92705

Plant Location:

Santa Fe Springs, CA

Standards:

NSF/ANSI 61 (2013) Section 5

Certificate:

Issued: 10/15/2014
Expires: 12/31/2019

Material/Product:

Hydrophobic Polyurethane Water Cut-Off, Dual Component System

Contact Temperature:

23 ± 2 °C


Models:

SealBoss 1510 WaterStopFoam F

SealBoss 1510 WaterStopFoam F is a drinking water system component in accordance with Standard NSF/ANSI 61 Section 5 (Issued 10/22/2013) when properly mix with SealBoss 15X Accelerator. ⁽¹⁾

SealBoss 15X Accelerator is a drinking water system component in accordance with standard NSF/ANSI 61 Section 5 (Issued 10/22/2013) when properly mixed with SealBoss 1510 WaterStopFoam F

Note ⁽¹⁾ See next page for additional information and restrictions.



THIS CERTIFICATION MARK MAY BE
APPLIED TO THE APPROVED PRODUCTS
AND TO THEIR PACKAGING OR
DESCRIPTIVE LITERATURE




ANSI Accredited Program
PRODUCT CERTIFICATION
ID #0303



ADDITIONAL INFORMATION

Company	SealBoss Corporation
Contact	Technical Support
Phone	(714) 662-4445
Product Description	Hydrophobic Polyurethane Water Cut-Off, Dual Component System
Brand Name/Model No.	SealBoss 1510 WaterStopFoam F
Material Characteristics	
Minimum tank size (gallons):	40,000
Max Surface Area/Vol ratio (sq in/L):	1.7
Colors:	Original
Method of how to prepare this application:	Refer to manufacturer's instruction for details.
Is Coating required (i.e. primer, Intermediate Coat, Top Coat, and thinner)	No
Number of Coats ⁽¹⁾	One
Description of substrate preparation (including use of specific thinner):	None
Type of thinner used:	None
Highest percentage of thinner use:	Not Applicable
Maximum crack fill width on a normal run ⁽¹⁾ (in)	0.25
Re-coat dry time/temperature:	None
Total cure time/temperature:	5 min/77 ± 5 °F up to 24 hours/77 ± 5 °F ⁽¹⁾
Shortest cure time between coats or layers	Not Applicable
Mix Ratio:	10:1:1 by weight (SealBoss 1510:SealBoss 15X Accelerator:Water)
If this paint/coating system is intended to be applied to pipe, would this be applied to as a:	
a. "Certified for use on new pipe?"	Not Applicable
b. "Certified for use on pipe intended for immediate return to service?"	Not Applicable
Flushing or preparation instruction prior to use:	Normal flush for a minimum 15 seconds at approximately 3 gpm water @ ambient temperature. Refer to Manufacturer's instruction for details.
Comments:	
WATER CONTACT RESTRICTION	
Contact Temperature	23 ± 2 °C
Contact Material:	Water

Note ⁽¹⁾: As Tested



THIS CERTIFICATION MARK MAY BE APPLIED TO THE APPROVED PRODUCTS AND TO THEIR PACKAGING OR DESCRIPTIVE LITERATURE



ANSI Accredited Program
PRODUCT CERTIFICATION
ID #0303