



TRUESDAIL LABORATORIES, INC.

# Product Listing

**For:**

Drinking Water System Components – Health Effects

**Company:**

SealBoss Corporation  
1669 E Wilshire Avenue  
Santa Ana, CA 92705

**Plant Location:**

Santa Fe Springs, CA

**Standards:**

NSF/ANSI 61 (2013) Section 5

**Certificate:**

Issued: 10/15/2014  
Expires: 12/31/2019

**Material/Product:**

Hydrophobic Polyurethane Water Cut-Off, Dual Component System

**Contact Temperature:**

23 ± 2 °C


**Models:**

SealBoss 1570 WaterStopFoam F

SealBoss 1570 WaterStopFoam F is a drinking water system component in accordance with standard NSF/ANSI 61 Section 5 (Issued 10/22/2013) when properly mix with SealBoss 15X Accelerator. <sup>(1)</sup>

SealBoss 15X Accelerator is a drinking water system component in accordance with standard NSF/ANSI 61 Section 5 (Issued 10/22/2013) when properly mixed with SealBoss 1570 WaterStopFoam F

Note <sup>(1)</sup> See next page for additional information and restrictions.



THIS CERTIFICATION MARK MAY BE  
APPLIED TO THE APPROVED PRODUCTS  
AND TO THEIR PACKAGING OR  
DESCRIPTIVE LITERATURE




ANSI Accredited Program  
PRODUCT CERTIFICATION  
ID #0303



**ADDITIONAL INFORMATION**

<b>Company</b>	SealBoss Corporation
Contact	Technical Support
Phone	(714) 662-4445
<b>Product Description</b>	Hydrophobic Polyurethane Water Cut-Off, Dual Component System.
Brand Name/Model No.	SealBoss 1570 WaterStopFoam F
<b>Material Characteristics</b>	
Minimum tank size (gallons):	20,000
Max Surface Area/Vol ratio (sq in/L):	2.1
Colors:	Original
Method of how to prepare this application:	Refer to manufacturer's instruction for details.
Is Coating required (i.e. primer, Intermediate Coat, Top Coat, and thinner)	No
Number of Coats <sup>(1)</sup>	One
Description of substrate preparation (including use of specific thinner):	None
Type of thinner used:	None
Highest percentage of thinner use:	Not Applicable
Maximum crack fill width on a normal run <sup>2</sup> (in)	0.25
Re-coat dry time/temperature:	None
Total cure time/temperature:	5 min/77 ± 5 °F up to 24 hours/77 ± 5 °F <sup>(1)</sup>
Shortest cure time between coats or layers	Not Applicable
Mix Ratio:	10:1:1 by weight (SealBoss1570:SealBoss 15X Accelerator:Water)
If this paint/coating system is intended to be applied to pipe, would this be applied to as a:	
a. "Certified for use on new pipe?"	Not Applicable
b. "Certified for use on pipe intended for immediate return to service?"	Not Applicable
Flushing or preparation instruction prior to use:	Normal flush for a minimum 15 seconds at approximately 3 gpm water @ ambient temperature. Refer to Manufacturer's instruction for details.
Comments:	
<b>WATER CONTACT RESTRICTION</b>	
Contact Temperature	23 ± 2 °C
Contact Material:	Water
Note <sup>(1)</sup> : As Tested	



THIS CERTIFICATION MARK MAY BE APPLIED TO THE APPROVED PRODUCTS AND TO THEIR PACKAGING OR DESCRIPTIVE LITERATURE



ANSI Accredited Program  
PRODUCT CERTIFICATION  
ID #0303