



TRUESDAIL LABORATORIES, INC.

Product Listing

For:

Drinking Water System Components – Health Effects

Company:

SealBoss Corporation
1669 E. Wilshire Avenue
Santa Ana, CA 92705, USA

Plant Location:

Santa Fe Springs, CA

Standards:

NSF/ANSI 61 Section 5 (Issued 10/22/2013)

Certificate Expires:

12/31/2019

Material/Product:

Hydrophilic Polyurethane WaterStop Cut-Off, Single Component System

Contact Temperature:

23 ± 2 °C

Models:

SealBoss FlexGel System ⁽¹⁾

Note ⁽¹⁾ See next page for additional information and restrictions.



THIS CERTIFICATION MARK MAY BE
APPLIED TO THE APPROVED PRODUCTS
AND TO THEIR PACKAGING OR
DESCRIPTIVE LITERATURE



ANSI Accredited Program
PRODUCT CERTIFICATION
ID #0303



ADDITIONAL INFORMATION

Company

Contact

Phone

Product Description

Brand Name/Model No.

Material Characteristics

Minimum tank size (gallons):

Max Surface Area/Vol ratio (sq in/L):

Colors:

Method of how to prepare this application:

Is Coating required (i.e primer, Intermediate Coat, Top Coat, and thinner)

Number of Coat²

Description of substrate preparation (including use of specific thinner):

Type of thinner used:

Highest percentage of thinner use:

Maximum crack fill width (inch) on a normal run²

Re-coat dry time/temperature:

Total cure time/temperature:

Shortest cure time between coats or layers

Mix Ratio:

If this paint/coating system is intended to be applied to pipe, would this be applied to as a:

a. "Certified for use on new pipe"?

b. "Certified for use on pipe intended for immediate return to service"?

Flushing or preparation instruction prior to use:

Comments:

WATER CONTACT RESTRICTION

Contact Temperature

Contact Material:

Note ⁽²⁾: As Tested

SealBoss Corporation

Technical Support

(714) 662-4445

Hydrophilic Polyurethane Watercut Cut-Off, Single component System.

SealBoss FlexGel System

20,000

2.1

Original

Refer to manufacturer's instruction for details.

No

One

None

None

Not Applicable

0.25

None

5 min/77±5°F up to 24 hr/77±5°F ⁽²⁾

Not Applicable

1:8 by weight (SealBoss FlexGel : Water)

Not Applicable

Not Applicable

Normal flush for a minimum 15 seconds at approximately 3 gpm water @ ambient temperature.

Refer to Manufacturer's instruction for details.

23 ± 2°C

Water