

SealBoss® FlexGel 2

RANGE OF APPLICATION

- Stop water infiltration
- Sealing joints
- Sealing of pipe joints through commercial packer equipment for repairing leakages in sanitary and storm sewer pipes
- Pipe Intrusions
- Sewers, Manholes, Utility Boxes
- Tunnels, Dams
- Soil Stabilization

TYPE OF MATERIAL

SealBoss® FlexGel 2 is a single component hydrophilic polyurethane grout. The product is capable of incorporating large amounts of water that are multiples of its own mass, thereby forming a water proofing gel. The cure time of the product is determined by the amount of water added and the temperature. When **SealBoss® FlexGel 2** comes in contact with only small amounts of water (up to three times by volume) the material reacts to a closed cell foam while expanding. The cured material is flexible. Since water is a component of the cured product structure, the material can be effected by wet and dry cycles. The reacted material may shrink and swell as a result of the surrounding moisture content.

The capability of the cured product to swell and increase in volume due to water absorption is one of the important features that discriminate hydrophilic grouts from their hydrophobic counterparts.

SealBoss® FlexGel 2 is designed as a single component material. To achieve most satisfying and permanent results in certain applications, a combination of **SealBoss® FlexGel 2** with other systems of our product line may be advised. Ask your **SealBoss** technician for details.

SealBoss® FlexGel 2 is certified for water contact in accordance with NSF standard 61, for contact with potable water.

PROCESSING

SealBoss® FlexGel 2 is a unique product in our line as it can either react to a foam or a gel on contact with water. The determining factor for the physical properties is the amount of water present during the reactive time. At a ratio of 1:4 to 1:15 (product to water) a gel is obtained. Lower water ratios result in a strong gel of a light cellular structure. The more water is added the gel gradually softens offering a solid non-cellular gel structure. The gel time is about 1 to 3 minutes varying with temperature and water saturation. At a ratio of 1:1 to 1:3 (product to water) **SealBoss® FlexGel 2** reacts to a foam with good tear resistance.


To fully make use of the **SealBoss® FlexGel 2** gel forming properties, the simultaneous injection of water may be advised. The presence of too little water may result in a foam which may or may not be desired. Two component equipment may be utilized to achieve a certain mixing ratio such as needed for the desired gel properties. The grout can be applied much in the same manner as acrylamide grout with the advantage of superior strength and better durability. The product may also be applied with single component injection equipment. Again, the presence of sufficient water is necessary for the product to

NSF Drinking Water Contact Approved Super Flexible, Hydrophilic Injection Gel

Certified for contact with potable water in accordance with NSF/ANSI-61 International Standard for Drinking Water Additives

form a gel. In some applications water may be introduced to the area prior to injection.

For 'curtain injection' behind below grade structures it is recommended to drill through the structure in a pattern that is determined by the physical properties of the soil. To create a standard pattern holes are drilled 50 cm (two feet) apart from each other in a horizontal line. The next step is to drill holes in a line 50 cm above the first line in the same fashion but staggered. Injection should begin at the highest point. Each packer should be injected until material penetrates the surrounding drill holes. After injection is complete packers should be removed and drill holes be filled with a cementitious grout. The picture indicates the drill hole pattern.



MAINTENANCE OF EQUIPMENT

Remove all excess product and any smears. Tools and mixing equipment must be cleaned immediately after use. **R70 Pump Flush** is good to your equipment and should always be used. For best results please follow our recommendations.

First Step is conditional - Omit if in conflict with regulations on the jobsite or the equipment you use: Flush first with a very small amount of solvent (not supplied by US) to cut remaining material. Caution: Xylol, Toluol, Acetone, M.E.K. are hazardous, combustible, aggressive towards the environment, equipment, seals and hoses. Immediately follow second step.

Second Step: Flush with **R70 Pump Flush** circulate cleaner through pump and hoses for several minutes at higher flow rates. **R70 Pump Flush** is a solvent free, non-flammable cleaner, lubricator and pump and hose conditioner. The product ships without hazard label. We assume no responsibility for equipment damaged by use of material.

PRECAUTION

Protect your health! While working with this material, safety goggles, gloves and safety clothing must be worn at all times. While injecting, a full face shield is strongly recommended. Spills and blow-outs do happen! Protect yourself and others on the jobsite. Consider property in proximity of the application area to prevent loss or damage. Protect your jobsite from unauthorized persons. Store all materials and equipment safely and out of reach of children!

Observe container labels, MSDS, and instructions in the Product Catalog before using the product and equipment. In case one of the components comes in contact with the skin, wash thoroughly with soap and water. Provide adequate ventilation in volume and pattern in working area. Further protection: emergency showers and eyewash stations.

SealBoss® FlexGel 2

**NSF Drinking Water Contact Approved
Super Flexible, Hydrophilic Injection Gel**

Certified for contact with potable water in accordance with NSF/ANSI-61 International Standard for Drinking Water Additives

TECHNICAL DATA	FLEXGEL2			
Appearance	Light Brown			
Color	Amber			
Solids	100%	ASTM D 1010		
Density, g/ml	1.1	ASTM D 3574		
Flash Point, C / F	>225	ASTM D 93-85		
Viscosity, cps at 40C-25C	390-750	ASTM D 1638-74		
Corrosiveness	Non-Corrosive			
Solubility in Water	Gelation			
Components	Polyurethane Resin			
Packaging	5 Gal			
	55 Gal			
Storage	Good storage stability for unopened containers at 15° - 30° C 58° - 85° F. Store indoors.			
Induction Time, 20C/68F	<30 sec			
Gel time, 25C/70F	approx. 100 sec			
Properties:				
Physical Form	Foam	Gel	Gel	
Water Ratio, approx.	1:1	1:5	1:8	
Tensile Strength, psi	430	165	150	ASTM D3574
Bonding Strength	300-380	120-150	120-140	
Tensile Elongation, %	462	>1250	>1250	ASTMD3574
Die-C	49	43	43	
Shrinkage	<1%-10% ASTM D1042 variable with water content and foam or gel reaction			
Appearance	Light Brown Foam - Gel			
	<p>Tested for contact with potable water in accordance with NSF Standard 61 ANSI/NSF 61 9R55 When mixed with water Max surface area 15cm²/ Liter Refer to PDS for mixing</p>			

Limited Warranty Policy and Disclaimer for Products Supplied and/or Distributed by SealBoss Corp.: All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty either expressed or implied. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any supplied materials relieves the user of the obligation to read and follow the warnings and instruction for each product as set forth in the current Technical Data Sheet, product label and Material Safety Data Sheet prior to product use. SealBoss Corp. warrants supplied / distributed products to be free of manufacturing defects. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of the manufacturer which proves to be defective. There are no other warranties by SealBoss Corp. of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. SealBoss Corp. shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty whether expressed or implied. SealBoss Corp. shall not be responsible for use of this product in a manner to infringe on any patent or any other intellectual property rights held by others. In addition, no warranty or guarantee is being issued with respect to appearance, color, fading, chalking, staining, shrinkage, peeling, UV damage, excessive temperature exposure, normal wear and tear or improper application by the applicator. Damage caused by abuse, neglect and lack of proper maintenance, acts of nature and / or physical movement of the substrate or structural defects are also excluded from the limited warranty. SealBoss Corp. reserves the right to conduct performance tests on any material claimed to be defective prior to any repairs by owner, general contractor, or applicator. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations and statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller. SealBoss Corp. reserves the right to change the properties of products without notice.

Revised 201203