


SealBoss® 1500 Hot Shot Cartridge



Product Data Sheet

**WaterStopFoam
2-Component Formula**

SealBoss® 1500 Applications

SealBoss® 1500 WaterStopFoam Cartridge

- Defective Concrete (Cracked or Honeycombed)
- Concrete Construction Joints & Cracks
- Limestone
- Basements, Parking Garages, Brick Construction
- Pipe Intrusions
- Tunnels, Dams, Bridges
- Sewers, Manholes, Utility Boxes

Water Activated, Polyurethane Waterstop & Seal Injection Foam Grout

SealBoss® 1500 WaterStopFoam Advantages:

- SealBoss® Product-Pump-Packer System Solution
- 1:1 Ratio, 2 Component Cartridge System Formula
- Unregulated For Transport
- Advanced Phthalate Free, MDI Formulation
- This Product is for Professional Use

Tips for Cartridge Users

- Shake cartridge prior to all applications and each time it is used for a minimum of 1 minute.
- Remove air from system - prime cartridge by slowly dispensing product from cartridge into mixer in vertical orientation until mixer is completely filled.
- Discard a small amount of product prior to application. Ratio may be slightly off when initial product travels through static mixer. Once uniform mixture is observed, product is ready for application.
- Dispensed product is highly water reactive and will expand to foam.

Product Description

SealBoss® 1500 WaterStopFoam is a hydrophobic, water-activated (hydro-active), water cut-off grout and foam seal grout based on a phthalate free, MDI polyurethane. The product is 100% solvent free, 100% solids two component formulation to be mixed at a 1:1 ratio by volume. Upon contact with water SealBoss® 1500 WaterStopFoam reacts to a semi flexible foam while expanding its volume 30 to 40 times. The cured material is of a constant volume. Since water is not a component of the foam structure, the cured material is essentially not effected by water or dryness. The reacted material essentially does not shrink or swell.

The advanced 1:1 formulation of the product results in a very dense, closed cell structure when injected under pressure. Very low counter pressure will result in a less rigid more expanded product. For best waterproofing results a closed cell structure is desired. |

Installation Guidelines

The product is part of the **SealBoss® Cartridge System**. The mix ratio by volume is 1:1. SealBoss® 1500 WaterStopFoam reacts with the moisture in the structure and does not need large amounts of water to react. Simultaneous injection of water is typically not necessary. If the area of application seems to be completely dry, pre-injection of water may be recommended in some circumstances.



SealBoss® 1500 Hot Shot Cartridge WaterStopFoam

SealBoss®

1500 Hot Shot Cartridge



Product Data Sheet
WaterStopFam
2-Component Formula

Technical Properties

	1500 Comp. A	1500 Comp. B
Appearance	Colorless	Brown
Solids	100%	100% ASTM D 2396
Density, lb/gal - g/ml	1.12	0.93 ASTM D 4569
Boiling Point, °C / °F	205°C / 400°F	170°C / 338°F
Flash Point, °C / °F	180°C / 356°F	125°C / 225°F ASTM D 93
Viscosity, cps	90-98	90-98 ASTM D 2196
Mixing Ratio, by Volume	1:1	
Solubility in Water	not	
Packaging	22 oz dual cartridge	
Storage / Shelf Life	Unopened Containers Only at 15-30°C / 58-85°F in dry, sun free indoors Cartridges - 12 months	Unopened Containers Only at 15-30°C / 58-85°F in dry, sun free indoors Cartridges - 12 months

Reaction

Induction Time, 20°C / 68°F	15 sec
Initial Cure Time, 20°C / 68°F	2 min

Properties Cured

Physical properties may vary based on water ratios & conditions	
Expansion, %	approx. 4000 (40 Times)
Elongation, %	10-20 ASTM D 3574
Tensile Strength	65 psi ASTM D 3574
Shear Strength	>15 psi
Strength (Sand Filled)	1500 psi
Corrosiveness	Non-Corrosive
Resistance	Resistant to Most Organic Solvents, Mild Acids, Alkali and Micro Organisms



Health and Safety

Protect your health! Always use safety gear in compliance with OSHA and all applicable local and job-site regulations While working with products. Handling of this product may result in spills, splashes, and airborne substances. Wear appropriate safety goggles, gloves and safety clothing at all times. During the pressure injection process a full face shield is advised for anybody within reach of product spill or blowout. Consider property in proximity of the application to prevent loss or damage. Protect jobsite from unauthorized persons. Store all materials and equipment safely and out of reach of children and animals! Observe container labels, SDS, applicable laws and regulations and all instructions before using the product and equipment. In case one of the components comes in contact with the skin, wash thoroughly with soap and water. Provide adequate ventilation in volume and pattern in working area. Further protection: emergency showers and eyewash stations. Get immediate medical attention as needed.

Limited Warranty Policy and Disclaimer for Products Supplied and/or Distributed by SealBoss Corp.: SealBoss Corp. Products are for Professional Use. All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty either expressed or implied. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any supplied materials relieves the user of the obligation to read and follow the warnings and instruction for each product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use. SealBoss Corp. warrants supplied / distributed products to be free of manufacturing defects. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of the manufacturer which proves to be defective. There are no other warranties by SealBoss Corp. of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. SealBoss Corp. shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty whether expressed or implied. SealBoss Corp. shall not be responsible for use of this product in a manner to infringe on any patent or any other intellectual property rights held by others. In addition, no warranty or guarantee is being issued with respect to appearance, color, fading, chalking, staining, shrinkage, peeling, UV damage, excessive temperature exposure, normal wear and tear or improper application by the applicator. Damage caused by abuse, neglect and lack of proper maintenance, acts of nature and / or physical movement of the substrate or structural defects are also excluded from the limited warranty. SealBoss Corp. reserves the right to conduct performance tests on any material claimed to be defective prior to any repairs by owner, general contractor, or applicator. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations and statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller. SealBoss Corp. reserves the right to change the properties of products without notice.

Revised 202501