

SealBoss® 1640 Dry & Wet Applications

- Leak Seal, Void Filler, Stabilizer
- Undersealing of Structures

Dry Reactive, Fast Cure, Hydrophobic
Two Component Polyurethane Foam & Seal
Injection Foam Grout

Seal - Fill - Densify

Product Description

SealBoss® 1640 is a closed cell, two-component, non-shrink polyurethane foam with structural properties. This MDI (methylene-diphenyl-isocyanate) based product is 100% solvent free and 100% solids. The product starts to react when mixed and does not need moisture from external sources for the reaction. SealBoss® 1640 expands up to eight times forming a closed cell structure and cutting down the material consumption drastically. The cured foam offers limited structural strength combined with increase in volume and excellent bonding properties on dry and with limitations on wet surfaces.

SealBoss® 1640 S is designed to fill voids in soil and stone, brick or concrete structures for the purpose of waterproofing as well as regaining certain structural strength. The excellent combination of hardness and flexibility qualifies SealBoss® 1640 for use in areas where structural strength and moderate flexibility are desired.

The expanding and compressive strength qualities of SealBoss® 1640 Structural Strength SlabLifter™ make it a price competitive alternative for the filling of voids and 'pockets'. The structural strength of the foam product is highly correlated to the expansion rate. SealBoss® 1640 Structural Strength SlabLifter™ can be applied in dry and wet areas. Additional moisture may increase the expansion. The standard mixture expands approximately six times in volume. Job site testing is recommended to determine product suitability. To achieve most satisfying and permanent results in certain applications, a combination of SealBoss® 1640 with other systems of our product line may be advised.


SealBoss® 1640 is not designed to stop high velocity water leaks. To stop active water leaks please refer to **SealBoss® 1510 Water Stop Foam**. Ask your SealBoss® technician for details. The product is for professional use.

Installation Guidelines

SealBoss® 1640 Structural Strength Foam is a two-component foam system. The mixing ratio is 1:1 (A:B) by volume. Condition the product to room temperature prior to use. The product is also available in bulk.



SealBoss® 1640 Structural Strength Leak Seal & Void Filler Foam Cartridge



Technical Properties

Components	TEST METHOD	COMP. A	COMP. B	COMP. A/B Mixed
Solids		100%	100%	
Viscosity A/B mixed	ASTM D 2196			280-400 mixed
Specific gravity	ASTM D 891	1.2	1.04	
Weight per gal, lb		10.0	8.68	
Mix ratio	by weight	52	48	
	by volume	50	50	
Cured Material				
Density		4 lbs/ft ³		
Compressive strength		11,520 psf (80 psi) (fully cured)		
Physical Properties				
Initial Reaction Time		5 seconds to 20 seconds (depending on temperature)		
Rise time, minutes		2-4		
Tack free time		60 seconds to 240 seconds (depending on temperature)		
Max. Expansion (unconfined)		20 times (2000%)		
Shrinkage		<1%		
Packaging				
Cartridge Systems		22 oz (650 ml)		
Bulk		5 gal	5 gal	
		55 gal	55 gal	
		Tote Tanks		
Storage		1 year. Unopened containers at 15-30°C, 58-85°F Store indoors		
		Cartridges: 9 months		
Corrosiveness		Non-Corrosive		
Appearance		Gold-Yellow		
		Polyurethane Foam		
Resistance to Chemicals		High Resistance to		
		Most Organic Solvents, Mild Acids, Alkali and		
		Micro Organisms Mild Acids, Alkali and Micro Organisms		

Health and Safety

Protect your health! Observe container labels, SDS, applicable laws and regulations and all instructions before using the product and equipment. Always use safety gear in compliance with OSHA and all applicable local and job-site regulations While working with products. Handling of this product may result in spills, splashes, and airborne substances. Wear appropriate safety goggles, gloves and safety clothing at all times. Protect jobsite from unauthorized persons. Store all materials and equipment safely and out of reach of children and animals! In case one of the components comes in contact with the skin, wash thoroughly with soap and water. Provide adequate ventilation in volume and pattern in working area. Further protection: emergency showers and eyewash stations. Get immediate medical attention as needed.



Limited Warranty Policy and Disclaimer for Products Supplied and/or Distributed by SealBoss Corp.: SealBoss Corp. Products are for Professional Use. All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty either expressed or implied. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any supplied materials relieves the user of the obligation to read and follow the warnings and instruction for each product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use. SealBoss Corp. warrants supplied / distributed products to be free of manufacturing defects. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of the manufacturer which proves to be defective. There are no other warranties by SealBoss Corp. of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. SealBoss Corp. shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty whether expressed or implied. SealBoss Corp. shall not be responsible for use of this product in a manner to infringe on any patent or any other intellectual property rights held by others. In addition, no warranty or guarantee is being issued with respect to appearance, color, fading, chalking, staining, shrinkage, peeling, UV damage, excessive temperature exposure, normal wear and tear or improper application by the applicator. Damage caused by abuse, neglect and lack of proper maintenance, acts of nature and / or physical movement of the substrate or structural defects are also excluded from the limited warranty. SealBoss Corp. reserves the right to conduct performance tests on any material claimed to be defective prior to any repairs by owner, general contractor, or applicator. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations and statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller. SealBoss Corp. reserves the right to change the properties of products without notice.

Revised 202501