



### SealBoss® SealPipe Kit Applications

- Annular Spaces
- Pipe Penetrations
- Large Cracks and Joints
- Small Void Filling
- Electrical Conduits
- Stops Additional Damage

### SealBoss® SealPipe Kit Advantages

- Fast Water Activated Polyurethane Foam Reaction
- Ease of Application - Hand Applied
- Versatile Application Range
- Applied in Wet Environments
- Moisture-activated in Dry Environments
- NSF 61 Potable Water Approved PU

### Kit Contents

**SealBoss® SealPipe Kit** contains all products you need for the application.

- 1 Pint Bottle: **SealBoss® 1510 Hydrophobic PU**
- 0.1 Pint Bottle: **SealBoss® 15x Catalyst**
- 1 Bag: **SealBoss® 1500 Seal Oakum**
- Disposable Gloves

### Application

1. Put on gloves and safety goggles.
2. Empty kit contents.
3. Thoroughly mix 15x Catalyst into pint bottle of 1510 Hydrophobic PU. Follow **SealBoss® 1510 WaterStopFoam** Data Sheet instructions.
4. Cap and shake the bottle.
5. In separate container, saturate desired amount of SealBoss® 1500 Seal Oakum with SealBoss® 1510/15x solution.
6. In wet environment, apply the SealBoss® 1500 Seal Oakum directly into the pipe penetration, crack, joint, or void and observe reaction.
7. In dry environment, briefly submerge in water prior to application of SealBoss® 1500 Seal Oakum, or apply SealBoss® 1500 Seal Oakum and then introduce water with spray bottle to initiate reaction.
8. For all applications, it is important to apply quickly as reaction effectively begins immediately.

### Health and Safety

Protect your health! Always use safety gear in compliance with OSHA and all applicable local and jobsite regulations while working with products. Handling of this product may result in spills, splashes, and airborne substances. Wear appropriate safety goggles, gloves and safety clothing at all times. Store all materials and equipment safely and out of reach of children and animals! Observe container labels, SDS, applicable laws

and regulations and all instructions before using the product and equipment. In case one of the components comes in contact with the skin, wash thoroughly with soap and water.



**Limited Warranty Policy and Disclaimer for Products Supplied and/or Distributed by SealBoss Corp.:** SealBoss Corp. Products are for Professional Use. All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty either expressed or implied. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any supplied materials relieves the user of the obligation to read and follow the warnings and instruction for each product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use. SealBoss Corp. warrants supplied / distributed products to be free of manufacturing defects. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of the manufacturer which proves to be defective. There are no other warranties by SealBoss Corp. of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. SealBoss Corp. shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty whether expressed or implied. SealBoss Corp. shall not be responsible for use of this product in a manner to infringe on any patent or any other intellectual property rights held by others. In addition, no warranty or guarantee is being issued with respect to appearance, color, fading, chalking, staining, shrinkage, peeling, UV damage, excessive temperature exposure, normal wear and tear or improper application by the applicator. Damage caused by abuse, neglect and lack of proper maintenance, acts of nature and / or physical movement of the substrate or structural defects are also excluded from the limited warranty. SealBoss Corp. reserves the right to conduct performance tests on any material claimed to be defective prior to any repairs by owner, general contractor, or applicator. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations and statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller. SealBoss Corp. reserves the right to change the properties of products without notice.

Revised 201705