

## To: Whom It May Concern

Our Lab ran VOC (Volatile Organic Component) test on SealBoss 6500 as per ASTMD2369.

## Procedure:

Dispense SealBoss 6500 A side and SealBoss 6500 B side threw cartridge using static mixer at 1:1 volume ratio on pre-weigh sample disk. Take weight of sample + sample disk and then we kept the sample in to oven@ 230 F for 1 hour. After 1 hour, cool the sample at room temp. for 30 minutes and reweigh the sample.

	Sample 1	Sample 2	Sample 3
Sample disk weight (grams)	54.2705	54.5415	54.6433
Sample disk weight +	67.2114	69.9742	72.3956
sample (grams)			
Sample disk weight =	67.2112	69.9741	72.3955
sample (grams)			
After 1 hr in oven @ 230F			
% Solid by weight	100	100	100
% Exempt solvent	0	0	0
% Water	0	0	0
Mixed Density	9.077	9.077	9.077
(pounds/gallon)			
VOC (Grams / Liter)	0	0	0

Limited Warranty Policy and Disclaimer for Products Supplied and/or Distributed by SealBoss Corp.: SealBoss Corp. Products are for Professional Use. All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty either expressed or implied. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any supplied materials relieves the user of the obligation to read and follow the warnings and instruction for each product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use. SealBoss Corp. warrants supplied / distributed products to be free of manufacturing defects. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of the manufacturer which proves to be defective. There are no other warranties by SealBoss Corp. of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. SealBoss Corp. shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty whether expressed or implied. SealBoss Corp. shall not be responsible for use of this product in a manner to infringe on any patent or any other intellectual property rights held by others. In addition, no warranty or guarantee is being issued with respect to appearance, color, fading, chalking, staining, shrinkage, peeling, UV damage, excessive temperature exposure, normal wear and tear or improper application by the applicator. Damage caused by abuse, neglect and lack of proper maintenance, acts of nature and / or physical movement of the substrate or structural defects are also excluded from the limited warranty. SealBoss Corp. reserves the right to conduct performance tests on any material claimed to be defective prior to any repairs by owner, general contractor, or applicator. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of or inability to use the product.